

ANMASI CURACIP ES 460
Antifoam emulsion for use in
waste water treatment and in the
metal processing industry

Supplier:
ANMASI A/S
Thorsvej 106
DK-7200 Grindsted

Your contact:
Anders Hedeby Sørensen
Tel.: 76 50 02 32
Mail.: ah@anmasi.dk

PRODUCT DESCRIPTION

Product data

Form:	liquid
pH-value:	7.2 – 7.5
Colour:	White - yellowish
Density g/cm ³ :	1,04 - 1,07 g/cm ³
Sensitive to cold below approx. °C:	+5°C

Properties

- Curatech ES 460 is a liquid formulation containing siloxane with highly foam depressant properties, both in a cold and warm state.
- The product does not have any disruptive impact on subsequent processes, such as powder coating, painting, galvanisation or hardening.

Application

- The application of Curatech ES 460 is quite manifold, e.g. in the areas of waste water treatment and in the metal processing industry.
- The dosing of Curatech ES 460 should be performed at a site with effective turbulence to assure an optimal blending with the cleaning solution.
- The application concentration typically is between 0.02 and 0.1 %.

ACOFT20.08.13

These notes are based on results gained from practical use to the present time. Taking into consideration individual operating conditions, deviations cannot be excluded. For this reason, we do not accept any third-party liability.