

ANMASI CURATECH NE 160 Low temperature spray cleaner with temporary corrosion protection

Fields of application:

Degreasing in spray cleaners and ultrasonic cleaning systems.

Supplier:

ANMASI A/S

Thorsvej 106

DK-7200 Grindsted

Your contact:

Anders Hedeby Sørensen

Tel.: 76 50 02 32

Mail.: ah@anmasi.dk

PRODUCT DESCRIPTION

Product data

Form:	liquid
pH-value:	9.0 – 9.6
Colour:	light yellow
Density g/cm ³ :	1,01 - 1,05 g/ml
Sensitive to cold below approx. °C:	+5°C

Properties

- Curatech NE 160 is a mildly alkaline cleaner, not subject to the obligation to label goods precisely, with temporary corrosion protection, for all types of material.
- Very good degreasing performance
- Oil and lubricants can be separated out with the help of a simple oil separator. This way, consistently good cleaning results can be achieved for several months.
- The detergent substances contained therein are biodegradable in accordance with EU guideline 648/2004.
- Curatech NE 160, furthermore, does not contain any NTA or EDTA and complies with Water Hazard Classification (WGK) 1.

Application

The concentration for use should be 4 - 5 %.

The washing cycle depends on the system and the soiling and typically is between 1 and 3 minutes.

Temperature

The application temperature should be between 40 - 55 °C.

Compatibility of materials

Chromium nickel steel, regular steel, aluminium, galvanised steel, non-ferrous metal, glass enamel, plastics etc.

ACOFT20.08.13

These notes are based on results gained from practical use to the present time. Taking into consideration individual operating conditions, deviations cannot be excluded. For this reason, we do not accept any third-party liability.