

ANMASI CURATECH PA 266  
Liquid, non-foaming anticorrosion agent  
for preventing the occurrence of flash  
rust on ferrous materials

Supplier:  
ANMASI A/S  
Thorsvej 106  
DK-7200 Grindsted

Your contact:  
Anders Hedeby Sørensen  
Tel.: 76 50 02 32  
Mail.: ah@anmasi.dk

## PRODUCT DESCRIPTION

### Product data

Form:	liquid
pH-value:	10.9 – 11.7
Colour:	clear
Density g/cm <sup>3</sup> :	1.01 - 1.04 g/ml
Sensitive to cold below approx. °C:	+5°C

### Properties

- The product is a liquid, non-foaming formulation for preventing the occurrence of flash rust on ferrous materials.
- The treated components dry off virtually stain-free.
- Curatech PA 266 solutions do not cause annoying foam.
- The product does not have any disruptive impact on subsequent processes, such as powder coating, painting, galvanisation or hardening.

### Application

The concentration for use should be 0.5 - 2.0 %.

### Temperature

The application temperature should be between 20 - 60 °C.

### Compatibility of materials

metal, steel and iron - cannot be used for aluminum and non-ferrous metals.

#### ACOFT20.08.13

These notes are based on results gained from practical use to the present time. Taking into consideration individual operating conditions, deviations cannot be excluded. For this reason, we do not accept any third-party liability.