

ANMASI CURATECH TN 401 Liquid, demulsifying wetting agent for use in an immersion process,

Supplier:
ANMASI A/S
Thorsvej 106
DK-7200 Grindsted

Your contact:
Anders Hedeby Sørensen
Tel.: 76 50 02 32
Mail.: ah@anmasi.dk

Fields of application:

It is used as a cleaning booster for the degreasing in an immersion process.

PRODUCT DESCRIPTION

Product data

Form:	liquid
pH-value:	8.6 - 9.9
Colour:	yellow - brown
Density g/cm ³ :	1.00 - 1.04 g/ml
Sensitive to cold below approx. °C:	+5°C

Properties

- Curatech TN 401 is a blend of non-ionic surfactants.
- The selection of a suitable builder framework should be made based on the operational requirements.
- Curatech TN 401 is ultra filterable.

Application

The duration of the washing cycle depends on the system and the soiling and typically is between 4 and 8 minutes.

The concentration for use should be 0.2 - 0.4 %.

Temperature

The application temperature should be between 40 - 70 °C.

Compatibility of materials

Chromium nickel steel, regular steel, aluminium, galvanised steel, non-ferrous metal, glass enamel, alkali-resistant plastics

ACOFT20.08.13

These notes are based on results gained from practical use to the present time. Taking into consideration individual operating conditions, deviations cannot be excluded. For this reason, we do not accept any third-party liability.