

ANMASI CURATECH TN 420 Liquid wetting agent for use in spray and injection flood cleaning processes

Fields of application:

It is used as a cleaning booster for the degreasing of iron, zinc, aluminium and brass.

Supplier:

ANMASI A/S
Thorsvej 106
DK-7200 Grindsted

Your contact:

Anders Hedeby Sørensen
Tel.: 76 50 02 32
Mail.: ah@anmasi.dk

PRODUCT DESCRIPTION

Product data

| | |
|-------------------------------------|------------------|
| Form: | liquid |
| pH-value: | 8.6 - 9.9 |
| Colour: | yellow - brown |
| Density g/cm ³ : | 1.00 - 1.04 g/ml |
| Sensitive to cold below approx. °C: | +5°C |

Properties

- Curatech TN 420 is a blend of non-ionic surfactants.
- The application of Curatech TN 420 takes place in a spray process and in an injection flood cleaning process.

Application

The duration of the washing cycle depends on the system and the soiling and typically is between 2 and 4 minutes.

The concentration for use should be 0.1 - 0.5 %.

Temperature

The application temperature should be between 55 - 70 °C.

Compatibility of materials

Chromium nickel steel, regular steel, aluminium, galvanised steel, non-ferrous metal, glass enamel, alkali-resistant plastics

ACOFT20.08.13

These notes are based on results gained from practical use to the present time. Taking into consideration individual operating conditions, deviations cannot be excluded. For this reason, we do not accept any third-party liability.