

ANMASI CURATECH TN 6221

Liquid, mildly alkaline
ultrasonic cleaner

Fields of application:

Components made of iron, aluminium, zinc and non-ferrous metals can be treated with this product.

Supplier:

ANMASI A/S
Thorsvej 106
DK-7200 Grindsted

Your contact:

Anders Hedeby Sørensen
Tel.: 76 50 02 32
Mail.: ah@anmasi.dk

PRODUCT DESCRIPTION

Product data

Form:	liquid
pH-value:	8.0 - 10.0
Colour:	yellow - brownish
Density g/cm ³ :	0.96 - 0.99 g/ml
Sensitive to cold below approx. °C:	+5°C

Properties

- Curatech TN 6221 is a blend of non-ionic surfactants and salts of organic acids.
- The application takes place in an ultrasonic process.
- After cleaning, the materials treated receive a temporary corrosion protection through adherence of a hydrophobic film.

Application

Curatech TN 6221 is used for the removal of greases, oils and polishing pastes.

The application concentration typically is between 2 and 5 %.

The cleaning time depends on the type and degree of soiling and typically is between 3 and 6 minutes.

Temperature

The cleaning temperature typically is between 50 °C and 70 °C.

Compatibility of materials

Chromium nickel steel, regular steel, aluminium, galvanised steel, non-ferrous metal, glass enamel, alkali-resistant plastics

ACOFT20.08.13

These notes are based on results gained from practical use to the present time. Taking into consideration individual operating conditions, deviations cannot be excluded. For this reason, we do not accept any third-party liability.